

The Z-2000P is a powerful entry level positive displacement dispensing system. Utilizing our proprietary pumping system, this machine is highly resistant to abrasion and chemically aggressive materials while providing extremely accurate and consistently repeatable 2-part dispensing.

The Z-2000P uses direct dial analog controls for reliable adjustment of rate, ratio and dispense time. Progressing cavity metering pumps provide precise mixing and continuous flow with accurate and repeatable results with every dispense. Exceptional results with Epoxy, Silicone and Urethane materials 2-part materials.



Specifications

Mix Ratios:	1:1 to 20:1
Viscosity Range:	1 to 50,000 cps
Flow rate:	0.05cc to 98cc per second
Shot size:	0.5cc to 500cc
Accuracy:	+/- <2%
Shop Air:	100 PSI <1 CFM
Power:	100 – 240 VAC Single Phase 50/60 Hz
Dimensions:	24" x 32" x 63"
Weight:	150 lbs.

Features

- Analog Control
- Discreet Shot Timer
- AC Motors and Drives
- 5 gallon Poly Reservoir tanks
- Dispense Head on Swing Arm
- Stand Alone Cart Mount
- Economical

Available Options

- 10 gallon Poly tanks
- Purge Timer
- In tank Agitation
- Desiccant Dryer